

4-Kant

E=Eckenmass

sw= Schlüsselweite

Theoretisches Eckmass: $E = sw \cdot \sqrt{2} = sw \cdot 1.4142$

Profil	Abmessung (sw) [mm]	Räumkapazität	Vorbohrung [mm]
4-Kant	1"-H9	25-60 mm	25.2 G9
4-Kant	¾"-H9	20-40 mm	18.80 G9
4-Kant	3/8" 9.52-H9	15-30 mm	9.50 H9
4-Kant	½" 12.7-H9	16-30 mm	12.60 G9
4-Kant	12.88/12.85 MM	26 mm	13.50 H9
4-Kant	3.55 +/-0.05	5-10 mm	3.55 H9
4-Kant	4-H9	16 mm	4.2 H9
4-Kant	4-H9	13 mm	4 H9
4-Kant	5.42/5.44	15 mm	5.30 G9
4-Kant	5-H9	9-32 mm	4.90 G9
4-Kant	5-H9	8-28 mm	4.90 G9
4-Kant	6.5-H9	18 mm	6.30 G9
4-Kant	6.5 x 6.2	24 mm	6.10 G9
4-Kant	6-H9	10-28 mm	5.90 G9
4-Kant	6-D8	2x15 mm	6.4 H9
4-Kant	7.2 +0.05-0	2X15 mm	7.60 H9
4-Kant	7-H9	20 mm	6.80 G9
4-Kant	8-H7	20 mm	7.90 G9
4-Kant	8-H9	12-30 mm	7.90 G9
4-Kant	8-H9	63 mm	9 H9
4-Kant	8-P9		8.00 P9
4-Kant	8.05 H9	21mm	8.00 H9
4-Kant	8.16		8.00 G9
4-Kant	9-H9	16-40 mm	9.00 H9
4-Kant	9.1 +/-0.05	26 mm	9.10 H9
4-Kant	9.1-H9	15-40 mm	9.10 H9
4-Kant	9.2/0+0.1	22 mm	9.10 G9
4-Kant	9-H8/E=Ø9.9	30 mm	8.8 G9
4-Kant	9-H9	24 mm	8.95 G9
4-Kant	9-H9 VB10	40mm	10 H9
4-Kant	10.1 +/-0.05	20 mm	10 G9
4-Kant	10-D8	30 mm	9.8 G9
4-Kant	10-E8	7-27 mm	9.8 G9
4-Kant	10-H9	60 mm Bronze	10.40 H9
4-Kant	10-H9	16-50 mm	9.90 G9
4-Kant	10-H9	24 mm Rostfrei	9.80 G9
4-Kant	10-H9	63 mm	11 H9
4-Kant	10-H9 /E=12.4	16-50 mm	9.90 G9
4-Kant	11-H9	16-24 mm	10.90 G9
4-Kant	11-H9	70 mm	12 H9
4-Kant	11-H9	63 mm	12 H9
4-Kant	12.55 + 0.1	18-50 mm	12.50 G9
4-Kant	12.7 D11	20-35 mm	12.75 G9
4-Kant	12.8/12.9	25 mm	12.80 H9
4-Kant	12-H9	16-50 mm	11.8 G9
4-Kant	12-H9	22-50 mm	11.80 G9

Die aufgelisteten Räumwerkzeuge stehen nicht zum Verkauf.

Profil	Abmessung (sw) [mm]	Räumkapazität	Vorbohrung [mm]
4-Kant	13-H9	18-50 mm	12.80 G9
4-Kant	14-H9	16-40 mm	14 H9
4-Kant	14-E10	20-40 mm	14 H9
4-Kant	14-H10	76 mm Rostfrei	14.50 G9
4-Kant	14.3/14.5	54 mm Bronze	14.20 G9
4-Kant	14-H9	20-50 mm	13.80 G9
4-Kant	15-H9	16-32 mm	14.90 G9
4-Kant	15.15-H9	25 mm	15.00 G9
4-Kant	16-H9	69 mm	15.90 G9
4-Kant	17.25/17.30	15-55 mm	17.60 H9
4-Kant	17+0.01/0.04 E= 22.5	25-60 mm	16.80 G9
4-Kant	17-E7	58 mm GGG 40	16.80 G9
4-Kant	17-H9	40 mm	16.80 G9
4-Kant	18.25/18.30 E=Ø23.2	22-64 mm	18.5 H9
4-Kant	18-H9	20-50 mm	17.80 G9
4-Kant	18-H9	36 mm	4 KT
4-Kant	19-H9	18-50 mm	18.70 G9
4-Kant	20.42/20.58	35 mm	20 H9
4-Kant	20-H9	28-60 mm	20 H7
4-Kant	20.1	11 mm	20 G9
4-Kant	21-H9	46 mm	20.70 G9
4-Kant	22-H9	36-80 mm	21.70 G9
4-Kant	24-H9	28-75 mm	23.80 G9
4-Kant	25-H9	65 mm	24.80 G9
4-Kant	26-H9	20-55 mm	25.70 G9
4-Kant	27-H9	20-54 mm	26.70 G9
4-Kant	28-H9 E=38	55 mm	27.70 G9
4-Kant	30-H9	82 mm	29.90 G9
4-Kant	31-H9	20-55 mm	31 H9
4-Kant	32-H9	25-66 mm	31.80 G9
4-Kant	35-H9	25-60 mm	34.70 G9
4-Kant	36-H9	25-60 mm	35.70 G9
4-Kant	38.2+0.1 R 1.5		38.00 G9
4-Kant	40-H9	28-70 mm	39.80 G9
4-Kant	42.1+0.1 R=1.5	70 mm	42 H9 G9
4-Kant	42-H9	28-70 mm	41.80 G9
4-Kant	46-H9	28-70 mm	45.80 G9
4-Kant	50-H9	28-60 mm	49.70 G9