

## 6-Kant

E=Eckenmass

sw= Schlüsselweite

Theoretisches Eckmass:  $E = sw \cdot 1.155$

Profil	Abmessung [mm]	Räumkapazität	Vorbohrung [mm]
6-Kant	1"-H9	30-75 mm	25.4 H9
6-Kant	¼"-H9	20-50 mm	6.35 H9
6-Kant	¾"-H9	70 mm	18.70 G9
6-Kant	4-H9	8-24 mm	3.95 G9
6-Kant	6.12/6.15	24 mm	6.00 G9
6-Kant	6-H9	24 mm	6.00 H9
6-Kant	7-E8	25 INOX	7 G9
6-Kant	7-H8	12-30 mm	6.80 G9
6-Kant	8-H9	18-70 mm	7.9 G9
6-Kant	10-H8	12-36 mm	9.80 G9
6-Kant	11-H9	25-90 mm	11 H9
6-Kant	12-E10	22 mm	12 H9
6-Kant	12-H9	14-60 mm	11.80 G9
6-Kant	13-H9	28-70 mm	12.80 G9
6-Kant	14.24 E=15.74	19 mm	14 G9
6-Kant	14-H9	18-45 mm	13.90 G9
6-Kant	15-H9	18-45 mm	14.75 G9
6-Kant	16-H9	18-50 mm	15.8 G9
6-Kant	17.1-H9	25-73 mm	17 G9
6-Kant	17-H9	25-73 mm	16.70 G9
6-Kant	17.5-H10	50 mm	17.5 G9
6-Kant	19-H9	76 mm	18.80 G9
6-Kant	20-H9	20-60 mm	19.80 G9
6-Kant	21-H9	20-60 mm	21.00 H9
6-Kant	22-H9	69 mm	21.80 G9
6-Kant	24.1 +0.1/-0	30-40 mm	24 H9
6-Kant	24-H9	25-85 mm	23.80 G9
6-Kant	25-H9	50 mm	24.70 G9
6-Kant	27-H9	32-80 mm	26.70 G9
6-Kant	27.2	14 mm	27.20 H9
6-Kant	28-H9	28-70 mm	
6-Kant	30-H8	25-70 mm	29.70 G9
6-Kant	31-H9	25-66 mm	30.80 G9
6-Kant	32 +0.03/+0.08	25-70 mm	31.70 G9
6-Kant	36-H9	20-60 mm	35.70 G9
6-Kant	41-H9	28-70 mm	41 H9
6-Kant	42-H9	30-90 mm	41.7 G9
6-Kant	46.25-H9	40 mm (Alu)	46 H9
6-Kant	50-G7	53 mm	49.70 G9

Die aufgelisteten Räumwerkzeuge stehen nicht zum Verkauf.